GR YARIS SPECIFICATIONS

| ENGINE | 1.6 Turbo | |
|---------------------------------|---|--|
| Engine code | G16E-GTS | |
| Туре | 3-cylinder in line | |
| Valve mechanism | DOHC 12-valve with Dual VVT-i | |
| Fuel system | Direct & indirect Injection, D-4ST high fuel pressure (20 Mpa) | |
| Supercharging | Single scroll turbo with ball bearings | |
| Displacement (cm ³) | 1.618 | |
| Bore x stroke (mm) | 87.5 x 89.7 | |
| Compression ratio (:1) | 10.5 : 1 | |
| Max. power (DIN hp/ kW @ rpm) | 261/192 @ 6,500 | |
| Max. torque (Nm @ rpm) | 360 @ 3,000 to 4,600 | |
| Emissions level | Euro 6d | |

| TRANSMISSION | | |
|----------------------------------|--|--|
| 4WD system type | GR Four Electronically-controlled multi-plate type clutch | |
| - Front/rear torque distribution | variable, 3 modes from 60/40 to 30/70 | |
| - Limited Slip Differentials | option Torsen front and rear | |
| Туре | Manual | |
| Gear ratios (:1) | | |
| - 1st | 3,538 | |
| - 2nd | 2,238 | |
| - 3rd | 1,535 | |
| - 4th | 1,162 | |
| - 5th | 1,081 | |
| - 6th | 0,902 | |
| - Reverse | 3,831 | |
| Differential gear ratio (:1) | 3.941 (1st to 4th) - 3.350 (5th-6th-Reverse) | |

| PERFORMANCE | | |
|-----------------------------|------------------------------|--|
| Weight/Power ratio (kg/hp) | 4,9 | |
| Max. speed (km/h) | 230 (electronically limited) | |
| Acc. 0 - 100 km/h (seconds) | 5,5 | |
| FUEL CONSUMPTION | | |
| WLT combined cycle (I/100) | 8,2 | |
| Fuel tank capacity (I) | 50 | |
| CO2 EMISSIONS (g/km) | | |
| WLT combined cycle | 186 | |
| NEDC combined cycle | 205 | |

| CHASSIS | | | |
|-----------------------------------|-----------------------|--|--|
| Front suspension | MacPherson Strut with | MacPherson Strut with reinforced lower arm | |
| - stabiliser bar diameter (mm) | Convenience Pack | Circuit Pack | |
| | 23,2 | 24,2 | |
| Rear suspension | Trailing doub | le wishbone | |
| - stabiliser bar diameter (mm) | 21 | 21 | |
| Steering | Rack & Pinion, Elect | Rack & Pinion, Electric Power Steering | |
| Overall ratio (:1) | 13, | 13,6 | |
| Lock to lock | 2,3 | 2,36 | |
| Min. turning circle tyre/body (m) | 10.6/* | 10.6/11.2 | |
| Brakes | | | |
| Front (diameter x thickness mm) | | Two piece ventilated, grooved disc (356 x 28) 4 pot aluminium monoblock caliper | |
| Rear (diameter x thickness mm) | | Ventilated grooved disc (297 x 18) 2 pot aluminium monoblock caliper | |
| Tyres | 225/40 ZF | 225/40 ZR18 92Y | |
| - Convenience Pack | Dunlop SP Spc | Dunlop SP Sport MAXX050 | |
| - Circuit Pack | Michelin Pilo | Michelin Pilot Sport 4S | |

| EXTERIOR DIMENSIONS (mm) | | |
|------------------------------|-------------|--|
| Overall length | 3.995 | |
| Overall width | 1.805 | |
| Overall height | 1.455 | |
| Wheelbase | 2.560 | |
| Front tread | 1.536 | |
| Rear tread | 1.572 | |
| Running ground clearance | 124 | |
| Cd (Drag coefficient) | 0,352 | |
| CARGO (dm3) | | |
| Capacity rear seats up (VDA) | 174 | |
| INTERIOR DIMENSIONS (mm) | | |
| Lenght | 1.880 | |
| Width | 1.430 | |
| Height | 1.175 | |
| | | |
| WEIGHT (kg) | | |
| Curb weight min/max | 1,280/1,310 | |
| Gross weight | 1.645 | |